



Mechanical Quick Hitch Connector Quick-change Excavator Attachments for 4-8 Ton Excavators

Our Product Introduction

for more products please visit us on excavatorlongarm.com

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: Zhonghe
- Certification: CE
- Minimum Order Quantity: 1 piece
- Price: \$220/pieces
- Packaging Details: wooden case
- Delivery Time: 7 work days
- Payment Terms: T/T
- Supply Ability: 50 Piece/Pieces per Month



Product Specification

- Type: Bucket Quick Hitch
- Part Name: Excavator Mechanical Quick Coupler
- Application: Excavator Attachment
- Material: Q355B
- Suitable Excavators: 4-8ton
- Weight: 200kg
- Color: Customers Requirements
- Warranty: 3 Months
- Condition: 100%new
- MOQ: 1 PCS
- Packing: Wodden Case / Container
- After-sales Service Provided: After-sales Service Available



More Images



Our Product Introduction

Product Description



Jiangmen Kaiping Zhonghe Machinery Manufacturing Co., Ltd

+86 13822325403

aria@excavatorlongarm.com

excavatorlongarm.com

9 Huancui West Road, Cuishanhu New Area, Kaiping City, Guangdong Province, China



Pin Grabber
Quick Hitch for
Excavator, also
call excavator
quick link, is
divided into
mechanical type
and hydraulic
type.

for more products please visit us on excavatorlongarm.com























It is composed of main support, movable block, hydraulic cylinder, pin shaft and other components. The use of quick joint in the replacement of various configurations, no need to depart pins manually, the excavator operator in the cabin gently move the switch to replace the attachment within 10 seconds, saving the time when replacing accessories, greatly improve the work efficiency.



PRODUCT DESCRIPTION

It is composed of main support, movable block, hydraulic cylinder, pin shaft and other components.

The use of quick joint in the replacement of various configurations, no need to depart pins manually, the excavator operator in the cabin gently move the switch to replace the attachment within 10 seconds, saving the time when replacing accessories, greatly improve the work efficiency.





CE certificat ion & Utility model patent certificat es



PACKING & SHIPPING
We use a variety of packing materials, including wooden crates, pallets, and other materials that are suitable for the specific product and shipment. Our team carefully inspects each package for quality assurance before shipping.



1. How do I start to order?

Firstly, talk to our sales about your machine model, working conditions, special needs and deadline. Then we will give you proposals FYR. You will receive a quotation within 24 Hours after confirming the proposal.

2. Why not have boom and stick cylinders in the plan?

A1: First, the whole long arm is lengthening, but the boom just lengthening from its middle sleeve to its end, so the original boom and stick cylinder can be used. Second, using the original parts can save your cost.

3. Are you always delivered on time?

We can't promise about the freight but what we can do is shortening our lead time

while keep the same quality level. So there will not be any problem even if the sea freight delay for a couple days. Our annual output of various types of excavator boom arms can reach 600 sets.

4. How long is the boom arm can mini excavator be be configured with? Whether it is necessary to increase the counterweight?

A2. Generally speaking, 30-40 excavator longest arm suggests to be 8 meters, can configure 0.1 cbm bucket, no need extra counterweight. 55 excavator longest arm suggests to be 12 meters, can configure 0.1-0.15 cbm bucket, need 0.5 ton extra counterweight. 60-80 excavator longest arm suggests to be 12 meters, can configure 0.15-0.25 cbm bucket, need 0.5-0.7 ton extra counterweight. It is not recommended to extend boom arm to longest length as min excavator is easy to sloshing.

5. How long will it takes to install a excavator long reach boom?

With reference to the efficiency of Chinese workers, and tools are fully prepared, it only takes one day to complete the disassembly and assembly. Kindly remind, prepare several containers to fill the oil before disassemble.

Recommended by seller

